

Cirago BTA6310 Micro USB Bluetooth® 3.0 Adapter

Benefits and Features

- Micro Design - RoHS compliant
- *Bluetooth* Specification 3.0 EDR – Class 1
- Enhanced Data Rate (EDR) compliant for both 2Mbps and 3Mbps modulation modes
- Supports Read Encryption Key Size: Enables a host to determine the negotiated encryption key size to determine security requirements
- Full speed *Bluetooth* operation with full Piconet and Scatternet support
- Support for 802.11 co-existence
- Full speed USB v 2.0 interface support OHCI and UHCI host interface
- Receiver Sensitivity -90dBm
- Stable, Accurate search ability
- Simplification of multi-link scenarios



Description	
Standard	<i>Bluetooth</i> 3.0 EDR, Class 1
Chipset	CSR BC04
Operating System Support	Windows 7, Vista, XP, 2000, Mac OS 10.4.7 or above, Linux
Drivers	Motorola Driver Suite
Operating Range	100 Meters (330ft)
Operating Frequency	2.4GHz - 2.4835 GHz ISM Band
RF Output Power	+15 dBm
Power Supply	USB powered, 5V
Dimensions	0.5" x 0.95" x 0.125" / 7" x 6" x 1" (Retail package)

Part number	UPC	Weight
BTA6310	858796050873	0.05 oz (unit) / 2.4 oz (retail pack)

Box Qty	Box Size
40 pcs	17" x 14" x 13"