

Bluetooth® 3.0 High Speed and Wi-Fi Combo Mini USB Adapter

BTA7300

Cirago Bluetooth 3.0 High Speed and Wi-Fi Combo Mini USB Adapter (BTA7300) is one of the only such devices on the market to combine the latest in Bluetooth 3.0 technology with 802.11n Wi-Fi capability on the same device. With an operating range of up to 33 feet, the Class 2 mini adapter supports Bluetooth data speed of up to 24 Mbps and Wi-Fi speed of up to 150 Mbps with zero interference between the two signals. The Cirago BTA7300 delivers up to eight times faster file transfer rate compared to Bluetooth 2.1 and Bluetooth 3.0 without High Speed.

When connected, the BTA7300 offers a simple solution allowing users to communicate to all the latest Bluetooth devices like mobile phones, PDAs, mice, keyboards, and printers for data transfer, networking and dial-up/fax functions without the need for cables.


Offering the latest generation in Bluetooth technology for faster speed and stable connectivity, the BTA7300 is also backward compatible, allowing users with older equipment to get the most out of their existing Bluetooth 2.1 technology. The BTA7300 is compatible with all editions of Windows 7, Vista and XP and installation is simple - simply plug the BTA7300 into an available USB port, insert the installation CD and go.



Bluetooth 3.0 High Speed 8x faster than Bluetooth 2.1



Wireless 802.11n



- Bluetooth 3.0 High Speed and Wi-Fi connection in one device
- Up to 8 times faster file transfer rate compared to Bluetooth 2.1 and Bluetooth 3.0 without High Speed
- Backwards compatible with Bluetooth 2.0
- Supports wireless 802.11n
- Bluetooth with 802.11 co-existence
- RoHS leadless material qualified
- Software and drivers included

Standard	Bluetooth 3.0 + High Speed, Class 2
Operating System Support	Windows 7, Vista and XP
Operating Range	Up to 10 Meters (33 Feet)
Operating Frequency	2.4GHz~2.4835GHz ISM Band
BT Transmitter Power	+4 dBm
Wi-Fi Transmitter Power	+12 dBm (b mode); +11 dBm (g mode); +10 dBm (n mode)
BT Receiver Sensitivity	-80 dBm @ 0.1% BER
Wi-Fi Receiver Sensitivity	-80 dBm (b mode); -77dBm (g mode); -64dBm (n mode)
Power Consumption	<300mA
Power Supply	USB powered, 5V
Accessories Included	BTA7300, Installation CD, Quick Start Guide
Dimension (L x W x D)	1.18" x 0.47" x 0.2"
UPC Code	858796051542



For more product information,
go to www.cirago.com



 **cirago**®